



2 MPP Trackers 150% DC Input Oversizing

Single Phase On-Grid Solar Inverter
XG3-10KTL

Efficient Higher Revenue

2 MPP Trackers , Max, input current per string: 20A
150% DC Input Oversizing
Compatible with high power modules

Reliable Worry Free

IP66 Protection Degree: support outdoor installation
AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

Intelligent Simple O&M

Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
Intelligent Fault Detection: AC side voltage and current waveforms real-time recorded, fast fault location
Support RS485/WiFi/4G: remote monitoring and operation via PC or mobile phones

Single Phase On-Grid Solar Inverter

	XG3KTL-2M	XG3.68KTL	XG4KTL	XG4.2KTL	XG4.6KTL	XG5KTL	XG6KTL	XG7KTL	XG8KTL	XG10KTL	XG7KTL1	XG8KTL1	XG10KTL1
	12kW												
Max. Input Power	4.5kW	5.52kW	6kW	6.3kW	6.9kW	7.5kW	9kW	10.5kW	12kW	15kW	10.5kW	12kW	15kW
Max. Input Voltage	600V												
Start Voltage	80V												
Rated Input Voltage	360V												
MPPT Voltage Range	50V ~ 550V												
Number of MPP Trackers	2												
Number of String per MPPT	1 / 1						1 / 2						
Max. Current per MPPT	20A						14A / 28						
Max.ShortCircuitCurrentperMPPT	26A						18.2A / 36.4A						

Output (AC)													
Max. Output Current	15A	16A	20A	20A	23A ^d	25A ^d	30A	35A	40A	45.5A	35A	40A	45.5A
Rated Output Power	3kW	3.68kW	4kW	4kW	4.6kW	5kW ^a	6kW	7kW	8kW	10kW	7kW	8kW	10kW
Max. Output Power	3.3kVA	3.68kVA	4.4kVA	4.4kVA	5kVA ^b	5.5kVA ^c	6.6kVA	7.7kVA	8.8kVA	10kVA	7.7kVA	8.8kVA	10kVA
Rated Grid Frequency	50Hz / 60Hz												
Rated Grid Voltage	220Vac / 230Vac / 240Vac												
Power Factor	>.99 (0.8 leading ~ 0.8 lagging)												
THDi	<3% (Rated Power)												

Efficiency														
Max. Efficiency	98.10%			98.30%				98.10%						
European Efficiency	97.30%			97.40%				97.30%						
MPPT Efficiency	99.90%													

Protection													
DC switch	Optional												
DC Reverse Polarity Protection	Yes												
Anti-islanding Protection	Yes												
AC short Circuit Protection	Yes												
ResidualCurrentMonitoring Unit	Yes												
InsulationResistanceMonitoring	Yes												
Ground Fault Monitoring	Yes												
Grid Monitoring	Yes												
PV String Monitoring	Yes												
Surge Protection	Yes												

Communication													
Display	LCD / LED+APP												
Communication	RS485 / WiFi / 4G												

Standard Compliance													
Certification	IEC/EN 62109-1/2, IEC/EN 61000-6-1/3, EN50549, IEC61727/IEC62116, CEI0-21, C10/C11, G98/G99, RD244, UNE217001, UNE217002, T0R Erzeuger, AS4777, ABNT, NB/T 32004												

General Data													
Dimensions (W x H x D)	380 x 380 x 160 mm												
Weight	13kg												
Operating Temperature Range	30° C ~ +60° C												
Cooling Method	Natural						Smart Cooling						
Protection Degree	IP66												
Max. Operating Altitude	4000m												
Relative Humidity	0 ~ 100%												
Topology	Transformerless												
Night Power Consumption	<1W												

● a: For AS4777, Rated Output Power of XG5KTL is 4999W. ● b: For VDE-AR-N 4105, Max. Output Power of XG4K6TL is 4600VA. For AS4777, Max. Output Power of XG4K6TL is 4999VA.
● c: For AS4777, Max. Output Power of XG5KTL is 4999VA. ● d: For AS4777, Max. Output Current of XG4K6TL and XG5KTL is 21.7A.